Printing date 29.09.2022 Version number 95 (replaces version 94) Revision: 30.03.2022 SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: TYRE SEALANT FORCE SERVICE-SPRAY 75 ML · Article number: K740652 · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Sector of Use SU21 Consumer uses: Private households / general public / consumers SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) · Product category Feed materials, Intermediates PC0 Other · Process category **PROC7** Industrial spraying **PROC11** Non industrial spraying · Application of the substance / the mixture Sealant · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: KCK Cyklosport-Mode s.r.o. Bartošova 348, 765 02 Otrokovice - Kvítkovice, Czech Republic Tel: +420 577 217 520 Identifikační číslo: 185 59 751 Mail: info@kckcyklosport.cz · Further information obtainable from: Department Product Safety • 1.4 Emergency telephone number: Tel: +420 577 217 520

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008




*

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.





· Signal word Danger

- Hazard statements
- H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
- · Precautionary statements
- *P101* If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

GB

Printing date 29.09.2022 Version number 95 (replaces version 94)

Revision: 30.03.2022

(Contd. of page 1)

Trade name: TYRE SEALANT FORCE SERVICE-SPRAY 75 ML

- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P260 Do not breathe spray.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- *P501* Dispose of contents / container in accordance with regional regulations.

• Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

*

*

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 74-98-6 EINECS: 200-827-9	propane 🚸 Flam. Gas 1A, H220	20-<25%
Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	Press. Gas (Comp.), H280	
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas 1A, H220 Press. Gas (Comp.), H280	12.5-<20%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas 1A, H220 Press. Gas (Comp.), H280	12.5-<20%
Addition at informations For	the wording of the listed hazard phrases refer to section 16	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- \cdot 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** *No further relevant information available.*

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -

(Contd. on page 3)

GB

Page 3/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.09.2022

Version number 95 (replaces version 94)

Revision: 30.03.2022

(Contd. of page 2)

Trade name: TYRE SEALANT FORCE SERVICE-SPRAY 75 ML

· Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
 Wear protective equipment. Keep unprotected persons away.
 Keep away from ignition sources.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. No special measures required.

- Information about fire and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- *Requirements to be met by storerooms and receptacles:* Observe official regulations on storing packagings with pressurised containers.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- 7.3 Specific end use(s) No further relevant information available.
- SECTION 8: Exposure controls/personal protection
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

• Appropriate engineering controls No further data; see item 7.

- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:
- Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

(Contd. on page 4)

Printing date 29.09.2022

Version number 95 (replaces version 94)

Revision: 30.03.2022

(Contd. of page 3)

Trade name: TYRE SEALANT FORCE SERVICE-SPRAY 75 ML

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

*

- Hand protection Not required.
- · Material of gloves Not required.
- · Penetration time of glove material Not required.
- Eye/face protection Not required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical p	properties
• General Information	
· Physical state	Aerosol
· Colour:	White
· Odour:	Odourless
· Odour threshold:	Not determined.
• Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling	
range	Not applicable, as aerosol.
· Flammability	Not applicable.
· Lower and upper explosion limit	* *
· Lower:	1.5 Vol %(106-97-8 butane (containing < 0,1 %
	butadiene (203-450-8)))
· Upper:	10.9 Vol % (74-98-6 propane)
· Flash point:	Not applicable, as aerosol.
· Ignition temperature:	365 °C (689 °F)
• Decomposition temperature:	Not determined.
· pH	Mixture is non-soluble (in water).
· Viscosity:	mixiure is non-soluble (in water).
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Dynamic: · Solubility	Noi determined.
•	Not missible on difficult to mix
• water: Partition coefficient a cotanol/water (log walks)	Not miscible or difficult to mix. Not determined.
• Partition coefficient n-octanol/water (log value)	
• Vapour pressure at 20 • C (68 • F):	3500 hPa (2625.2 mm Hg)
• Density and/or relative density	0.7 - (-3)(5.9) + (-1)
• Density at 20 •C (68 •F):	$0.7 \ g/cm^3 (5.8 \ lbs/gal)$
Relative density	Not determined.
· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Aerosol
· Important information on protection of health an	
environment, and on safety.	-
• Explosive properties:	Not determined.
· Solvent content:	
· Organic solvents:	50.0 %
· Water:	36.2 %
\cdot VOC (EC)	
	478.9 g/l
· VOC-EU%	50.00 %
· Solids content:	13.8 %
· Sound content:	13.0 /0
	(Contd. on page 5)

(Contd. on page 5)

Printing date 29.09.2022

Version number 95 (replaces version 94)

Revision: 30.03.2022

Trade name: TYRE SEALANT FORCE SERVICE-SPRAY 75 ML

	(Contd. of pag
Change in condition	
Evaporation rate	Not applicable.
Information with regard to physical hazard o	classes
• Explosives	Void
· Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised container:
	May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
• Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flamm	able
gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Skin corrosion/irritation No irritant effect.
- Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 6)

GB

Printing date 29.09.2022

Version number 95 (replaces version 94)

Revision: 30.03.2022

Trade name: TYRE SEALANT FORCE SERVICE-SPRAY 75 ML

(Contd. of page 5)

- · 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- \cdot 12.7 Other adverse effects
- \cdot Additional ecological information:
- · General notes:

*

*

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations. Disposal must be made according to official regulations.

SECTION 14: Transport information	
· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1950
	011720
· 14.2 UN proper shipping name · ADR	1950 AEROSOLS
·IMDG	AEROSOLS
· IATA	AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR	
· Class	2 5F Gases.
· Label	2.1
· IMDG, IATA	
· Class	2.1 Gases.
· Label	2.1
· 14.4 Packing group	
· ADR, IMDG, IATA	not regulated
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Gases.
• Hazard identification number (Kemler code):	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1
	litre: Category A. For AEROSOLS with a capacity

Page 7/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.09.2022

Version number 95 (replaces version 94)

Revision: 30.03.2022

Trade name: TYRE SEALANT FORCE SERVICE-SPRAY 75 ML

	(Contd. of page
	above 1 litre: Category B. For WASTE AEROSOLS:
	Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1
	litre:
	Segregation as for class 9. Stow "separated from" clas 1 except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
14.7 Maritime transport in bulk accord	ing to IMO
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (\widetilde{EQ})	Code: E0
· · · · · · ·	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	IL
Excepted quantities $(\widetilde{E}Q)$	Code: E0
	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P3a FLAMMABLE AEROSOLS

 \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

 \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· LIST OF SUBSTANCES SUBJECT TO AUTHORISATION (UK ANNEX XIV)

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.H280 Contains gas under pressure; may explode if heated.

(Contd. on page 8)

GB

Page 8/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.09.2022

Version number 95 (replaces version 94)

Revision: 30.03.2022

Trade name: TYRE SEALANT FORCE SERVICE-SPRAY 75 ML

	(Contd. of pa
	bbreviations and acronyms:
	ID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning th
In	nternational Transport of Dangerous Goods by Rail)
ю	CAO: International Civil Aviation Organisation
A.	DR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the
In	nternational Carriage of Dangerous Goods by Road)
IA	MDG: International Maritime Code for Dangerous Goods
IA	ATA: International Air Transport Association
G	HS: Globally Harmonised System of Classification and Labelling of Chemicals
E	INECS: European Inventory of Existing Commercial Chemical Substances
E.	LINCS: European List of Notified Chemical Substances
C	AS: Chemical Abstracts Service (division of the American Chemical Society)
V_{i}	OC: Volatile Organic Compounds (USA, EU)
P_{i}	BT: Persistent, Bioaccumulative and Toxic
vl	PvB: very Persistent and very Bioaccumulative
F	lam. Gas 1A: Flammable gases – Category 1A
A	erosol 1: Aerosols – Category 1
P	ress. Gas (Comp.): Gases under pressure – Compressed gas
*	Data compared to the previous version altered.