Printing date 27.09.2017 Version number 197 Revision: 18.09.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: CLEANER-SPRAY FORCE FOR BRAKES 200 ML
- · Article number: K895631
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- Product category PC35 Washing and cleaning products (including solvent based products)
- · Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- · Application of the substance / the mixture Cleaning agent/ Cleaner
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

KCK Cyklosport-Mode s.r.o.

Bartošova 348,

765 02 Otrokovice - Kvítkovice,

Czech Republic

Tel: +420 577 217 520

Identifikační číslo: 185 59 751

Mail: info@kckcyklosport.cz

- · Further information obtainable from: Department Product Safety
- 1.4 Emergency telephone number: Tel: +420 577 217 520

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 27.09.2017 Version number 197 Revision: 18.09.2017

Trade name: CLEANER-SPRAY FORCE FOR BRAKES 200 ML

(Contd. of page 1)

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

EC number: 921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-	50-<75%
Reg.nr.: 01-2119475514-35	hexane	
	③ Flam. Liq. 2, H225	-
	♦ Asp. Tox. 1, H304	
	Aquatic Chronic 2, H411	
	♦ Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 74-98-6	propane	10-<12.5%
EINECS: 200-827-9	♦ Flam. Gas 1, H220	
Index number: 601-003-00-5	Press. Gas C, H280	
Reg.nr.: 01-2119486944-21		
CAS: 106-97-8	butane	5-<10%
EINECS: 203-448-7	♦ Flam. Gas 1, H220	
Index number: 601-004-00-0	Press. Gas C, H280	
Reg.nr.: 01-2119474691-32		
CAS: 75-28-5	isobutane	5-<10%
EINECS: 200-857-2	♦ Flam. Gas 1, H220	
Index number: 601-004-00-0	Press. Gas C, H280	
Reg.nr.: 01-2119485395-27		
CAS: 124-38-9	carbon dioxide	2.5-<5%
EINECS: 204-696-9	Press. Gas L, H280	-

GB ·

Printing date 27.09.2017 Version number 197 Revision: 18.09.2017

Trade name: CLEANER-SPRAY FORCE FOR BRAKES 200 ML

(Contd. of page 2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.

(Contd. on page 4)

Printing date 27.09.2017 Version number 197 Revision: 18.09.2017

Trade name: CLEANER-SPRAY FORCE FOR BRAKES 200 ML

(Contd. of page 3)

· Storage class: 2 B

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

124-38-9 carbon dioxide

WEL Short-term value: 27400 mg/m³, 15000 ppm Long-term value: 9150 mg/m³, 5000 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Not required.

Printing date 27.09.2017 Version number 197 Revision: 18.09.2017

Trade name: CLEANER-SPRAY FORCE FOR BRAKES 200 ML

(Contd. of page 4)

SECTION 9: Physical and chemi	······································
9.1 Information on basic physical and c	hemical properties
General Information	
Appearance:	4 1
Form:	Aerosol Clear
Colour: Odour:	Solvent-like
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	101 determined.
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	
	<0°C (<32 °F)
Flash point:	Not applicable, as aerosol.
Flammability (solid, gas):	Not applicable.
Ignition temperature:	>200°C (>392 °F)
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	0.6Vol %
Upper:	10.9Vol %
Vapour pressure at 20°C (68 °F):	8hPa (6 mm Hg)
Density at 20°C (68 °F):	0.64g/cm³ (5.34 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	89.3%
EU-VOC:	622.1 g/l
EU-VOC in %:	97.50 %
VOC (EC)	(22) //
VOC FUR	622.1 g/l
VOC-EU%	97.50 %
Solids content:	0.0%
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

(Contd. on page 6)

Printing date 27.09.2017 Version number 197 Revision: 18.09.2017

Trade name: CLEANER-SPRAY FORCE FOR BRAKES 200 ML

(Contd. of page 5)

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Oral	LD50	>5,840 mg/kg (rat)
		>2,920 mg/kg (rab)
Inhalative	LC50 / 4h	>25.2 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

EC50 / 48 h | 3 mg/l (daphnia magna) EC50 / 72 h | 30-100 mg/l (algae)

LC50 / 96 h | 11.4 mg/l (fish)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 7)

Printing date 27.09.2017 Version number 197 Revision: 18.09.2017

Trade name: CLEANER-SPRAY FORCE FOR BRAKES 200 ML

(Contd. of page 6)

 $\cdot \textbf{12.6 Other adverse effects} \ \textit{No further relevant information available}.$

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
14 06 03*	other solvents and solvent mixtures
15 01 04	metallic packaging
15 01 11*	metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers

- · Uncleaned packaging:
- · Recommendation: Non contaminated packagings may be recycled.

· 14.1 UN-Number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR	1950 AEROSOLS, MARINE POLLUTANT/ ENVIRONMENTALLY HAZARDOUS
· IMDG · IATA	AEROSOLS, MARINE POLLUTANT AEROSOLS, flammable
· 14.3 Transport hazard class(es)	2 - 2 - 12 · 10 · 10 · 10 · 10 · 10 · 10 · 10 ·
$\cdot ADR$	
*	
· Class	2 5F Gases.
· Label	2.1
· IMDG	
· Class	2.1
· Label	2.1
· IATA	
· Class	2.1

(Contd. on page 8)

 Printing date 27.09.2017
 Version number 197
 Revision: 18.09.2017

Trade name: CLEANER-SPRAY FORCE FOR BRAKES 200 ML

	(Contd. of page
14.5 Environmental hazards: Marine pollutant: Special marking (ADR):	Yes Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	warning. Gases.
EMS Number:	F-D,S-U
Stowage Code	SWI Protected from sources of heat.
Siowage Couc	SW22 For AEROSOLS with a maximum capacity of 1 litre
	Category A. For AEROSOLS with a capacity above 1 litre
	Category B. For WASTE AEROSOLS: Category C, Clear
	of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre
	Segregation as for class 9. Stow "separated from" class 1
	except for division 1.4. For AEROSOLS with a capacity
	above 1 litre: Segregation as for the appropriate
	subdivision of class 2. For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Ani	nex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	IL
Excepted quantities (\widetilde{EQ})	Code: E0
	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/
G	ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

GB

Printing date 27.09.2017 Version number 197 Revision: 18.09.2017

Trade name: CLEANER-SPRAY FORCE FOR BRAKES 200 ML

(Contd. of page 8)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure - Compressed gas

Press. Gas L: Gases under pressure – Liquefied gas

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* Data compared to the previous version altered.

GB